

Version 1.02 Revision Date 26.07.2010

1. Identification of the substance/mixture and of the company/undertaking

Trade name Gearbox Oil 80W-90

Synonyms Gearbox Oil 80W-90, Gear Oil

Company Sasol Oil

32 Hill Street Randburg, 2125 Republic of South Africa

Information (Product safety) Telephone: +27 11 889 7600 / 0860 72765 Fax: +27 11 889

7979

E-mail address msds.info@sasol.com

Europe, Israel, Africa, Americas +44 (0)1235 239 670

Middle East, Arabic African

+44 (0)1235 239 671

countries

 Asia Pacific
 +65 3158 1074

 China
 +86 10 5100 3039

 South Africa
 +27 (0)17 610 4444

 Australia
 +61 2 9032 0460

2. Hazards identification

Identification of the risks

R45 May cause cancer.

3. Composition/information on ingredients

Preparation on the base:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Contents: 95.10 %W/W

CAS-No. 64742-54-7 **Index-No.** 649-467-00-8 **EC-No.** 265-157-1

Symbol(s) T R-phrase(s) -R45

For the full text of the R-phrases mentioned in this Section, see Section 16.

4. First aid measures

Inhalation Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial respiration.

Print Date 26.07.2010 10000006806 1/6



Version 1.02 Revision Date 26.07.2010

If symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water. If skin

irritation persists, call a physician. For thermal burns, cool affected areas as quickly as possible by immersing in water.

Consult a physician.

Eye contact Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician immediately. If burns

occur, treat as thermal burns.

Ingestion If swallowed, seek medical advice immediately and show this

container or label. Do NOT induce vomiting. Prevent vomiting if possible. If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an

unconscious person.

5. Fire-fighting measures

Suitable extinguishing

media

Water spray, Foam, Dry powder, Carbon dioxide (CO2)

Specific hazards during

fire fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment for

equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information Cool containers / tanks with water spray. In the event of fire

and/or explosion do not breathe fumes. Exposure to decomposition products may be a hazard to health.

6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Remove all

sources of ignition. Do not breathe vapours or spray mist.

Environmental

precautions

Prevent product from entering drains. Prevent further leakage or

spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material and dispose of as

hazardous waste.

Additional advice Never return spills in original containers for re-use.

7. Handling and storage

Handling

Safe handling advice Ensure adequate ventilation. Do not breathe vapours or spray

mist. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has



Version 1.02 Revision Date 26.07.2010

occurred. Wear personal protective equipment.

Advice on protection Keep away from open flames, hot surfaces and sources of

against fire and explosion ignition.

Storage

Requirements for storage Keep containers tightly closed in a cool, well-ventilated place.

areas and containers

8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

EUROPEAN OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Gloves suitable for permanent contact:

Material: butyl-rubber Break through time: 4 h Material thickness: 0.5 mm

unsuitable gloves

Material: Polyvinylchloride, leather, nitrile rubber/nitrile latex,

natural rubber/natural latex

Eye protection Safety glasses with side-shields

Skin and body protection Safety shoes, Lightweight protective clothing, Use protective

skin cream before handling the product.

Hygiene measures Wash hands before breaks and immediately after handling the

product.

Protective measures Wear suitable protective equipment.

9. Physical and chemical properties

Form liquid



Version 1.02 Revision Date 26.07.2010

state of matter liquid; at 20 °C; 1,013 hPa

Colourlight brownpourpoint-27 °CFlash point242 °CAutoignition temperature> 320 °C

Density 0.89 g/cm3; 20 °C

Water solubility emulsifiable

Viscosity, kinematic 145 mm2/s; 40 °C

10. Stability and reactivity

Materials to avoidOxidizing agentsHazardousCarbon oxidesdecomposition productsHydrocarbons

11. Toxicological information

Further information No data available

12. Ecological information

Ecotoxicity effects

Further information No data available

13. Disposal considerations

Product Dispose of in accordance with local regulations.

Contaminated packaging Store containers and offer for recycling of material when in

accordance with the local regulations.

14. Transport information

Further information Not classified as dangerous in the meaning of transport

regulations.

15. Regulatory information

Labelling



Version 1.02

Revision Date 26.07.2010



Regulatory base 1999/45/EC Symbol(s) T: Toxic

R-phrase(s) R45: May cause cancer.

S-phrase(s) S53: Avoid exposure - obtain special instructions before use.

S35: This material and its container must be disposed of in a

safe way.

S36/37: Wear suitable protective clothing and gloves.

Special labelling of certain mixtures

Restricted to professional users.

Hazardous components which must be listed on

the label

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified

16. Other information

Full text of R-phrases referred to under sections 2 and 3

R45 May cause cancer.

All reasonable efforts were exercised to compile this SDS in accordance with ISO 11014 and ANSIZ400.1.1993. The MSDS provides information regarding the health, safety and environmental hazards, at the date of issue, to facilitate the safe receipt, use and handling of the product in the workplace. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which the product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which the product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place as regards health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of the product.



Version 1.02

Revision Date 26.07.2010

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy or assume any liability for the incompleteness of the information contained herein or any advice given. The product is sold and risk passes in accordance with the specific terms and conditions of sale.

The MSDS was created by: B.SHAMASE The MSDS was approved by: Samson Mkwanazi